

Maintenance chart

| Grease | | | | Change fluid | | | | |
|--|---|--------|---|--------------|----------|--|--|--|
| Check | | | | Γ | R | Replace | | |
| Cleaning | | | | | | Drain fluid | | |
| Service_Points |] | | | | | Page Nb. | | |
| EVERY 10 HOURS OR DAILY | | | | | | | | |
| Clean tracks and components | x | | | T | | Clean tracks and components | | |
| Wheels and tires | | Х | | | | Wheels and tires | | |
| Engine and hydraulic coolers | | х | | | | Engine and hydraulic coolers | | |
| Engine coolant level | П | х | | | | Engine coolant level | | |
| Engine oil level | | х | | | | Engine oil level | | |
| Loader arm pivot points, coupler pins, and cylinder pins | | 1 | х | | | Loader arm pivot points, coupler pins, and cylinder pins | | |
| Hydraulic oil level | | х | | | | Hydraulic oil level | | |
| Loader arm and bucket hydraulic interlock | | X | | | | Loader arm and bucket hy- draulic interlock | | |
| INITIAL 50 HOURS | | | | | | | | |
| Final drive oil (track models) | | | > | | | Final drive oil (track models) | | |
| EVERY 50 HOURS | 3 | | | | <u>'</u> | | | |
| Cab intake filter | | Х | | | | Cab intake filter | | |
| Alternator and air conditioning compressor (if equipped) belt tension (models SR130, SR160, SR175, and SV185 only) | | x | | | | Alternator and air conditioning compressor (if equipped) belt tension (models SR130, SR160, SR175, and SV185 only) | | |
| Roll Over Protective Structure (ROPS) mechanism and hardware check | | x | | | | Roll Over Protective Structure (ROPS) mechanism and hardware check | | |
| EVERY 250 HOURS | | | | | | | | |
| In-line fuel filter (models SR130 and SR160 only) | | | | × | | In-line fuel filter (models SR130 and SR160 only) | | |
| Fuel prefilter | | | | | X | Fuel prefilter | | |
| Drive chain tension check | | x | | | | Drive chain tension check | | |
| EVERY 500 HOUR | S | | | | | | | |
| Engine oil and filter | | |) | (| | Engine oil and filter | | |
| Fuel prefilter | | | | X | | Fuel prefilter | | |
| Fuel filter | | | | × | | Fuel filter | | |
| Hydraulic oil filter | | | | × | | Hydraulic oil filter | | |
| Final drive chain tank oil | | x | | | | Final drive chain tank oil | | |
| Air cleaner elements | | | | × | | Air cleaner elements | | |
| Hardware - loose or damaged | | x | | | | Hardware - loose or damaged | | |
| Final drive oil (track models) | | $_{-}$ | > | (| | Final drive oil (track models) | | |
| EVERY 1000 HOURS | | | | | | | | |



| Grease | | | Change fluid | | | | |
|---|---|--|--------------|---|---|---|--|
| Check | | | | | R | eplace | |
| Cleaning | | | | | | Drain fluid | |
| Service_Points | | | | | | Page Nb. | |
| Hydraulic fluid and filter | | | | | Х | Hydraulic fluid and filter | |
| Final drive chain tank oil | | | | | Х | Final drive chain tank oil | |
| Oil Mist Separator (OMS) filter (models SR130, SR160, SR175, and SV185 only) | | | | x | | Oil Mist Separator (OMS) filter (models SR130, SR160, SR175, and SV185 only) | |
| EVERY 2000 HOURS | | | | | | | |
| Engine cooling system - Change fluid – SR130, SR160, SR175, and SV185 only | | | x | | | Engine cooling system - Change fluid - SR130, SR160, SR175, and SV185 only | |
| Engine cooling system - Change fluid – SR210, SR240, SV280, TR270, and TR310 only | | | x | | | Engine cooling system - Change fluid - SR210, SR240, SV280, TR270, and TR310 only | |
| Blow-by recirculation system (models SR210, SR240, SV280, TR270, and TR310 only) | | | | x | | Blow-by recirculation system (models SR210, SR240, SV280, TR270, and TR310 only) | |
| EVERY 4000 HOURS | | | | | | | |
| Diesel Particulate Filters (DPF) - Cleaning (models SR130 and SR160 only) | x | | | | | Diesel Particulate Filters (DPF) - Cleaning (models SR130 and SR160 only) | |
| AS REQUIRED | | | | | | | |
| Auto-regeneration | x | | | | | Auto-regeneration | |
| Manual regeneration | x | | | | | Manual regeneration | |