

Maintenance chart

			Change flui					id
						flu	ıid	
					pla	се		
				irea	se			
			Check Cleaning					
Service_Interval	Page Nb.	Service_Points	Nb. of pts					
INITIAL 10 HOURS	Operating Instructions	Wheel bolt and nut torque			X			
	Alter- nator and air condi- tioning com- pres- sor (if equippe belt tension	Alternator and air conditioning compressor (if equipped) belt tension for models SR130, SR160, SR175, and SV18 5 only			X			
EVERY 10 HOURS OR DAI- LY	Clean tracks and compo- nents	Clean tracks and components		X				
	Engine and hy- draulic coolers	Engine and hydraulic coolers			X			
	Engine coolant level	Engine coolant level			X			
	Engine oil level	Engine oil level			X			
	Lift arm, pivot points, coupler pins and cylin- der pins	Lift arm, pivot points, coupler pins and cylinder pins				X		
	Hy- draulic oil level	Hydraulic oil level			X			



			Change flu Drain fluid Replace Grease Check					
Service_Interval	Page Nb.	Service_Points	Nb. of pts					
	Seat belt, re- straint bar, and seat in- terlock oper- ation check	Seat belt, lap bar and seat interlock operation check		×				
INITIAL 50 HOURS	Final drive chain tank oil	Final drive chain tank oil		×				
EVERY 50 HOURS	Cab in- take fil- ter	Cab intake filter		×				
	Alter- nator and air condi- tioning com- pres- sor (if equipper belt tension	Alternator and air conditioning compressor (if equipped) belt tension for models SR130, SR160, SR175, and SV18 5 only		×				
	Roll Over Pro- tective Struc- ture (ROPS) mech- anism and hard- ware check	Roll Over Protective Structure (ROPS) mechanism and hardware check		*				



			Change				e flu	ıid	
					Drair		Jid		
					Repla	се	1		
				hec	ease]			
			Cleanii	_	, K				
Service_Interval	Page Nb.	Service_Points	Ni o pt	o. f					
INITIAL 100 HOURS	Final drive oil (track mod- els)	Final drive oil (track models)							X
EVERY 250 HOURS	In-line fuel fil- ter	In-line fuel filter for models SR130 and SR160 only					X		
	Fuel pre- filter	Fuel prefilter						X	
	Drive chain tension check	Drive chain tension check			X				
EVERY 500 HOURS	Engine oil and filter	Engine oil and filter							X
	Fuel pre- filter	Fuel prefilter					X		
	Fuel fil- ter	Fuel filter					X		
	Hy- draulic oil filter	Hydraulic oil filter					X		
	Final drive chain tank oil	Final drive chain tank oil			×				
	Air clean- er ele- ments	Air cleaner elements					X		
	Hard- ware - loose or dam- aged	Hardware - loose or damaged			X				



	Char							id
			Dra Rep				ıid	
			G	rea		CE		
		Cle	Che	eck				
Service_Interval	Page Nb.	Service_Points	Nb. of pts					
	Final drive oil (track mod- els)	Final drive oil (track models)						X
EVERY 1000 HOURS	Hy- draulic sys- tems - Change fluid	Hydraulic fluid and filter						X
	Final drive chain tank oil	Final drive chain tank oil						X
	Oil Mist Sepa- rator (OMS) filter	Oil Mist Separator (OMS) filter for models SR130, SR160, SR175, and SV185					X	
EVERY 2000 HOURS	Engine coolant drain and flush	Engine coolant drain and flush						X
	Blow- by re- circula- tion fil- ter	Blowby re-circulation filter for models SR210, SR220, SR250, SV250, SV300, TR270, TR320, and TV380 only					X	
EVERY 4000 HOURS	Diesel Partic- ulate Filter (DPF)	Diesel Particulate Filter (DPF)					X	
AS REQUIRED	Diesel Partic- ulate Filter (DPF)	Diesel Particulate Filter (DPF)		X				