

Maintenance chart

			Change fluid					
			Drain fluid Replace				id	
			Grease Check					
Service_Interval	Page	Service_Points	leaning Nb.					
Service_Interval	Nb.	Service_Points	of pts					
INITIAL 10 HOURS	Operat- ing In- struc- tions	Wheel bolt and nut torque			X			
	Alter- nator and air condi- tioning com- pres- sor (if equipped belt tension	Alternator and air conditioning compressor (if equipped) belt tension for models SR130, SR160, SR175, and SV18 5 only			X			
EVERY 10 HOURS OR DAI- LY	Clean tracks and compo- nents	Clean tracks and components		Х				
	Engine and hy- draulic coolers	Engine and hydraulic coolers			X			
	Engine coolant level	Engine coolant level			Х			
	Engine oil level	Engine oil level			Х			
	Lift arm, pivot points, coupler pins and cylin- der pins	Lift arm, pivot points, coupler pins and cylinder pins				X		
	Hy- draulic oil level	Hydraulic oil level			Х			

1



			Change flu				
				n fluid			
			G	ace			
			Che				
		Cle	aning				
Service_Interval	Page Nb.	Service_Points	Nb. of pts				
	Seat belt, re- straint bar, and seat in- terlock oper- ation check	Seat belt, lap bar and seat interlock operation check		X			
INITIAL 50 HOURS	Final drive chain tank oil	Final drive chain tank oil		X			
EVERY 50 HOURS	Cab in- take fil- ter	Cab intake filter		X			
	Alter- nator and air condi- tioning com- pres- sor (if equipped belt tension	Alternator and air conditioning compressor (if equipped) belt tension for models SR130, SR160, SR175, and SV18 5 only		X			
	Roll Over Pro- tective Struc- ture (ROPS) mech- anism and hard- ware check	Roll Over Protective Structure (ROPS) mechanism and hardware check		X			



			Change fluid						id	
			Drai				flu	lid		
					Re	pla	се			
				G	rea	se				
				Che	ck					
			Clea	aning						
Service_Interval	Page Nb.	Service_Points		Nb. of pts						
INITIAL 100 HOURS	Final drive oil (track mod- els)	Final drive oil (track models)								X
EVERY 250 HOURS	In-line fuel fil- ter	In-line fuel filter for models SR130 and SR160 only						Х		
	Fuel pre- filter	Fuel prefilter							Х	
	Drive chain tension check	Drive chain tension check				Х				
EVERY 500 HOURS	Engine oil and filter	Engine oil and filter								Х
	Fuel pre- filter	Fuel prefilter						Х		
	Fuel fil- ter	Fuel filter						Х		
	Hy- draulic oil filter	Hydraulic oil filter						Х		
	Final drive chain tank oil	Final drive chain tank oil				Х				
	Air clean- er ele- ments	Air cleaner elements						Х		
	Hard- ware - loose or dam- aged	Hardware - loose or damaged				х				

3



			Change fluid					d
							id	
				Rep	olad	ce		
			G	reas	se			
			Che	eck				
			aning	,				
Service_Interval	Page Nb.	Service_Points	Nb. of pts					
	Final drive oil (track mod- els)	Final drive oil (track models)						×
EVERY 1000 HOURS	Hy- draulic sys- tems - Change fluid	Hydraulic fluid and filter						×
	Final drive chain tank oil	Final drive chain tank oil						×
	Oil Mist Sepa- rator (OMS) filter	Oil Mist Separator (OMS) filter for models SR130, SR160, SR175, and SV185					X	
EVERY 2000 HOURS	Engine coolant drain and flush	Engine coolant drain and flush						X
	Blow- by re- circula- tion fil- ter	Blowby re-circulation filter for models SR210, SR220, SR250, SV250, SV300, TR270, TR320, and TV380 only					X	
EVERY 4000 HOURS	Diesel Partic- ulate Filter (DPF)	Diesel Particulate Filter (DPF)					X	
AS REQUIRED	Diesel Partic- ulate Filter (DPF)	Diesel Particulate Filter (DPF)		x				